

CARPET BROKERS



LenoFlooring
Vinyl Innovation

PRODUCT RELEASE

LENO NATURA
MARCH 2025

PRODUCT SPECIFICATIONS

LVT Dryback

UV Coating

Wear Layer

PVC Decor Film

PVC Middle Layer

Bottom Layer



PRODUCT SPECIFICATIONS

- TYPE OF INSTALLATION: Glue
- APPLICATION : Heavy Residential / Medium Commercial
- WEAR LAYER THICKNESS: 0,4 mm
- OVERALL THICKNESS: 2 mm
- PLANK SIZE: 1530 mm x 236 mm
- QUANTITY PER BOX: 5.777m²
- NUMBER OF PLANKS: 16 planks per box
- VOC TESTED: Floor Score Certified
- CASTOR CHAIR USE: non-staining wheels (EN425)
- COLOUR FASTNESS: 6 or above
- SURFACE TEXTURE: Ultra Matt

PRODUCT WARRANTY

- 15-year limited residential and an 8-year limited light commercial warranty
- The warranty applies to manufacturing defects on the product and not on the installation.
- The moisture warranty excludes damage resulting from mold and/or mildew growth due to prolonged exposure to moisture.
- This warranty does not cover flooding.

Terms and conditions apply.

CARE INSTRUCTIONS

This product range must be maintained in accordance with the Leno care and maintenance instructions.

- For indoor use only.
- Remove dust with a vacuum, mop with a mild soapy solution and damp mop.
- After mopping, ensure the floor dries completely. Standing water can damage vinyl floors, so it's crucial to dry the surface thoroughly.
- Abrasive chemicals such as detergents, soaps, "mop-and-shine" products, waxes, polishes, abrasive pads or cleaners, including nylon scouring pads, steel wool, Comet™, Soft Scrub™ not recommended as it may damage the finish.
- Do not use any type of polishing or buffing machine to clean the floor.

AVAILABLE ONLINE AND IN-STORE



LenoFlooring
Vinyl Innovation